directbrand™

the DEFENDER *the* PATRIOT

Dear Customer
Thank you for buying a Direct Brand Silicon Nitride MOS1 igniter. This product is light, hard, and has low thermal expansion coefficient. It has high mechanical strength, high fracture toughness, and it is resistant to deformation at room temperature as well as at elevated temperatures.

⚠ WARNING

Fire Hazard
Under no circumstances exceed the specified voltage.
Ensure that component does not come into direct contact with water (for example, spray, dripping water or rain).
Improper and dangerous operation can result from wiring errors. Ensure that wiring is routed and securely attached.

Shock Hazard
Always turn off electric power before working on any appliance.

Explosion Hazard
Shut off gas to appliance before installation begins, and do not reconnect until installation is complete.

FOR INSTALLATION BY QUALIFIED SERVICE PERSONNEL

Follow the recommended fitting instructions carefully. Failure to do so will void the warranty and may lead to injury or damage to property.

1) Disconnect gas and power supply.
2) Remove gas bottle from unit.
3) Remove mosquito net.
4) Remove the unit from its base. Turning unit upside down, remove the screws that secure the green top to the body. Turning the unit upright again, carefully separate the two halves.
5) Locate and unplug the igniter from the printed circuit board.

Please note that minor variations in configuration may occur depending on your model of Mosquito Magnet®

FITTING INSTRUCTIONS
Mosquito Magnet® Replacement Gas Igniter

Steps 1, 2, 3 and 4


Steps 5 and 6


Step 7


Steps 8 and 9 then 10, 11 and 12

6) Unscrew the igniter.
7) Remove old igniter and discard.
8) Place the new igniter into its housing and secure with screw, ensure all wires are safely routed.
9) Plug the igniter into the printed circuit board.
10) Replace the green top ensuring it fits securely and re-fasten in reverse sequence to No 4).
11) Reconnect power supply and gas.
12) Switch Mosquito Magnet® on and check for correct operation.

Direct Brand Limited · 11b Depot Street · South Grafton · MA 01560 · Fax 508-519-0397

directbrand™

the LIBERTY *the* MIDGE MASTER

Dear Customer
Thank you for buying a Direct Brand Silicon Nitride MOS1 igniter. This product is light, hard, and has low thermal expansion coefficient. It has high mechanical strength, high fracture toughness, and it is resistant to deformation at room temperature as well as at elevated temperatures.

⚠ WARNING

Fire Hazard
Under no circumstances exceed the specified voltage.
Ensure that component does not come into direct contact with water (for example, spray, dripping water or rain).
Improper and dangerous operation can result from wiring errors. Ensure that wiring is routed and securely attached.

Shock Hazard
Always turn off electric power before working on any appliance.

Explosion Hazard
Shut off gas to appliance before installation begins, and do not reconnect until installation is complete.

FOR INSTALLATION BY QUALIFIED SERVICE PERSONNEL

Follow the recommended fitting instructions carefully. Failure to do so will void the warranty and may lead to injury or damage to property.

1) Disconnect gas and power supply.
2) Remove gas bottle from unit.
3) Remove mosquito net.
4) Remove the unit from its base. Turning unit upside down, remove the screws that secure the green top to the body. Turning the unit upright again, carefully separate the two halves.
5) Locate and unplug the igniter from the printed circuit board.

© directbrand 2014

FITTING INSTRUCTIONS
Mosquito Magnet® Replacement Gas Igniter

Steps 1, 2, 3 and 4



Steps 5 and 6



Step 7



Steps 8 and 9 then 10, 11 and 12

6) Unscrew the igniter.
7) Remove old igniter and discard.
8) Place the new igniter into its housing and secure with screw, ensure all wires are safely routed.
9) Plug the igniter into the printed circuit board.
10) Replace the green top ensuring it fits securely and re-fasten in reverse sequence to No 4).
11) Reconnect power supply and gas.
12) Switch Mosquito Magnet® on and check for correct operation.

Direct Brand Limited · 11b Depot Street · South Grafton · MA 01560 · Fax 508-519-0397